

(+48) 32 453 91 70 🖂 info@pol-eko.com.pl www.pol-eko.com.pl POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

Data sheet

Laboratory Incubator CLW 1000 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen

- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarmAdmin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download



Smart PRO - preview screen






TECHNICAL DATA

air convection	forced
chamber capacity [l]	1005
working capacity [I]	1005
controller	microprocessor PID
display	7" full colour touch screen
TEMPERATURE	
temperature range [°C]	5°C above ambient temperature +100°C
temperature resolution every [°C]	0,1
temperature fluctuation at 37°C [+/-°C]*	0,2
temperature variation at 37°C [+/-°C]*	1,0
temperature protection	class 3.1 to DIN 12880
CHAMBER	
door type	double(5) / door with viewing window (option)
interior	
Smart PRO	acid-proof stainless steel to DIN 1.4301
IG Smart PRO	acid-proof stainless steel to DIN 1.4301
housing	
Smart PRO	powder coated sheet
IG Smart PRO	stainless steel linen finish

overall dims [mm] /1/

1260 2000	
1040	
1610	
600	
	600



shelves (standard max)	6 22
- reinforced shelf version (PW) [kg] /3/	100
max unit workload [kg]	300
- reinforced unit version (W) [kg] /4/	300
weight [kg]	319





ELECTRICAL PARAMETERS

voltage**	230V 50-60Hz	
nominal power [W]	1900	
warranty	24 months	
manufacturer	POL-EKO	

all the above technical data refer to standard units (without optional accessories)

* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K= +/- (T average max. - T average min.) / 2

** - other power supplies on request

1 - depth doesn't include 50 mm of power cable, the width does not include the 20 mm of rubber plug

2 - on uniformly loaded surface

3 - reinforced shelf

4 - additional internal glass door

OPTIONS AND ACCESSORIES

ſ.,		
Ľ	y	

INOX

Order number: */P INOX

Order number: */PP

Order number: */A

Order number: */PW

||+||

HEPA

>0<

Order number: KUW GN*/*

Order number: OWW/OWW LED

Order number: PT 100

Order number: HEPA

Order number: BRT/*/L or IQ/OQ/PQ

4

ALARM

Order number: BPP 12

Order number: PORT ALARM

door with viewing window

Stainless steel wire shelf INOX

Perforated shelf

Reinforced shelf

Stainless steel cuvettes

Interior lighting

Additional temperature sensor

HEPA Clean Air Filter

Calibration and IQ, OQ, PQ qualification

Battery backup for display

Dry alarm contact

 Bank: ING BŚ o/Wodzisław Śląski
 Nr rachunku:
 90 1050 1403 1000 0022 0879 5498
 Nr rej. w BD0 000005609

 NIP: 647-216-26-87
 REGON:
 276111984
 Sąd Rejonowy w Gliwicach, X Wydział Gospodarczy
 KRS 0001009595





60mm

100mm

(((●)))

Order number: OCZ/20	

Order number: OCZ/30

Order number: LANK

Order number: OCZ/60

Order number: OCZ/100

Order number: KD

LAN cable

Non-standard access port 20 mm

Additional access port 30 mm

Non-standard access port 60 mm

Non-standard access port 100 mm

Access control

